



FL327B

Polyester floor standing enclosure, Orion.Plus, plain door 1200x850x300 mm

Technical properties

Functions Cover with overpressure release Configuration Number of modules Compatibility Suitable for lightning protection Electric current Rated current	No No 630 A
Cover with overpressure release Configuration Number of modules Compatibility Suitable for lightning protection Electric current	259 No
Configuration Number of modules Compatibility Suitable for lightning protection Electric current	259 No
Compatibility Suitable for lightning protection Electric current	No
Compatibility Suitable for lightning protection Electric current	No
Suitable for lightning protection Electric current	
Electric current	
	630 A
Rated current	630 A
Dimensions	
Insertion depth	300 mm
Depth of installed product	300 mm
Internal depth	300 mm
Height of installed product	1200 mm
Width of installed product	850 mm
Thickness of sidewall material	2 mm
Cover, door	
Type of door closing	Barrel lock
Interlockable	Yes
Cover type	Closed (plain)
Door leave	single
Transparent cover or door	No
Materials	
Colour	RAL 7035
Colour	light grey
RAL colour	RAL 7035 - Light grey
Material	glas reeinforced polyester
Type of surface treatment	powder-coated
Installation, mounting	
Suitable for outdoor use	Yes

Equipment

Number of rows	7
Quantity of section in width	1
Number of keys	2
Number of openings for flange plates	0
Extension possible	No
Standards	
European directive WEEE	concerned
Safety	
Protection class	isol.class II
REACH conform	No
RoHS conform	Yes
Fire resistance	-