



VF212TJ



Small distributor,golf,flush,2row,24M,IP40,MS-terminal,N+PE,transparent door

Technical properties

Architecture

| | |
|-------------|----------------|
| Fixing mode | flush-mounting |
|-------------|----------------|

Functions

| | |
|---------------------|-----|
| With a pipe-in lead | Yes |
|---------------------|-----|

Configuration

| | |
|-------------------|----|
| Number of modules | 24 |
|-------------------|----|

Main electrical features

| | |
|-----------------|-------|
| Nominal voltage | 400 V |
|-----------------|-------|

Electric current

| | |
|---------------|------|
| Rated current | 63 A |
|---------------|------|

Dimensions

| | |
|-----------------------------|---------|
| Insertion depth | 72 mm |
| Depth of wall niche | 72 mm |
| Depth of installed product | 97.5 mm |
| Internal depth | 97.5 mm |
| Height of installed product | 418 mm |
| Installation height | 382 mm |
| Width of installed product | 382 mm |
| Built-in height | 382 mm |
| Built-in width | 318 mm |

Cover, door

| | |
|------------------------------------|----------------|
| Identification of protection index | 40 |
| Interlockable | No |
| Number of keylock of the door | 0 |
| Cover type | Closed (plain) |
| Door locking | without |
| Door leave | single |
| Cover type | Door |
| Transparent cover or door | Yes |

Materials

| | |
|------------|-----------------------|
| Colour | pure white |
| Colour | white |
| RAL colour | RAL 9010 - Pure white |

| | |
|-----------------------------------------------|---------------------------|
| Material | plastic |
| Type of surface treatment | untreated |
| Installation, mounting | |
| Suitable for outdoor use | No |
| Settings | |
| Enclosure type | Distributor empty cabinet |
| Equipment | |
| Number of rows | 2 |
| Quantity of section in width | 1 |
| Quantity of rails | 2 |
| Can be accessorized | Yes |
| Number of openings for flange plates | 0 |
| Extension possible | Yes |
| Earthing terminal block | Yes |
| Neutral terminal block | Yes |
| Signal passing door | Yes |
| Standards | |
| GWT Glow wire test | 650 °C |
| European directive WEEE | concerned |
| Safety | |
| IK protection code against mechanical impacts | IK07 |
| Protection index IP | IP40 |
| Protection class | isol.class II |
| REACH conform | No |
| RoHS conform | Yes |
| Halogen free | Yes |
| Use conditions | |
| Operating temperature | -25...40 °C |